



Since 1978

2 Year Warranty

Made in KOREA
Ridden by the WORLD

S&T Motors
HYOSUNG

2014 FULL LINE UP



ST7 DELUXE



MODEL

COLOR RANGE

TYPE

DISPLACEMENT

BORE x STROKE

COMPRESSION RATIO

MAX POWER

MAX TORQUE

FUEL SYSTEM

LUBRICATION

CLUTCH

GEAR

FINAL DRIVE

OVERALL LENGTH

OVERALL HEIGHT

OVER WIDTH

WHEEL BASE

GROUND CLEARANCE

SEAT HEIGHT

BRAKE

SUSPENSION

TIRE

FUEL TANK CAPACITY

CURB WEIGHT

Liquid cooled DOHC 8-valve 90 V-twin

682,2cc

81,5 x 65

11,5 : 1

67,1hp (46,0Kw) / @8,000RPM

42,3lb-ft (57,3Nm) / @7,000RPM

Fuel Injection

Wet Sump

Wet, Multiplate

Constant mesh 5-speed (1down 4up)

Belt

2470mm (97,24inch)

1290mm (50,79inch)

960mm (37,79inch)

1690mm (66,53inch)

155mm (6,10inch)

675mm (27,38inch)

F) 300Ø Semi floating single disc, 4 pistons caliper

R) 270Ø Single disc, 2 pistons caliper

F) 41Ø Conventional Telescopic

R) Swing arm with Hydraulic Double shock absorber (Preload adjustable)

F) 120/80-16 60H, R) 170/80-15 77H

17L (4,49gal)

265kg (584,24lbs)



ST7



Liquid cooled DOHC 8-valve 90 V-twin
682,2cc
81,5 x 65
10,3 : 1

67,1hp (46,0Kw) / @ 8,000RPM
42,3lb-ft (57,3Nm) / @ 7,000RPM

Fuel Injection
Wet Sump
Wet, Multiplate
Constant mesh 5-speed (1down 4up)
Belt

2470mm (97,24inch)
1135mm (44,68inch)
960mm (37,79inch)
1690mm (66,535inch)
155mm (6,10inch)
675mm (27,38inch)

F) 300Ø Semi floating single disc, 4 pistons caliper
R) 270Ø Single disc, 2 pistons caliper
F) 41Ø Conventional Telescopic
R) Swing arm with Hydraulic Double
shock absorber (Preload adjustable)

F) 120/80-16 60H, R) 170/80-15 77H
17L (4,49gal)
244kg (537,94lbs)



GV650P-Aquila



Liquid cooled DOHC 8-valve 90 V-twin
647cc
81,5 x 62
11,5 : 1

73,1hp (54,5Kw) / @ 9,000RPM
45,8lb-ft (62,1Nm) / @ 7,500RPM

Fuel Injection
Wet Sump
Wet, Multiplate
Constant mesh 5-speed (1down 4up)
Belt

2330mm (91,73inch)
1150mm (45,27inch)
840mm (33,07inch)
1670mm (65,75inch)
140mm (5,51inch)
690mm (27,16inch)

F) 300Ø Semi floating single disc, 2 pistons caliper
R) 270Ø Single disc, 2 pistons caliper
F) 41Ø Upside down Telescopic
Compression, Rebound damping adjustable)
R) Swing arm with Hydraulic Double
shock absorber (Preload adjustable)

F) 120/70-ZR-18 59W, R) 180/55 ZR-17 73W
16L (4,23gal)
239kg (526,91lbs)



GV250-Aquila



Air/Oil cooled DOHC 8-valve 75 V-twin
249cc
57 x 48,8
10,3 : 1

25,2hp (18,79Kw) / @ 9,000RPM
15,2lb-ft (20,63Nm) / @ 8,500RPM

Fuel Injection
Wet Sump
Wet, Multiplate
Constant mesh 5-speed (1down 4up)
Chain

2382mm (93,78inch)
1096mm (43,15inch)
875mm (34,45inch)
1515mm (59,65inch)
150mm (5,91inch)
710mm (27,95inch)

F) 275Ø Single disc, 2 pistons caliper
R) Drum
F) 41Ø Conventional Telescopic
R) Swing arm with Hydraulic Double
shock absorber (Preload adjustable)

F) 110/90-1659S, R) 150/80-15 70S
14L (3,70gal)
176kg (388,02lbs)



MODEL

COLOR RANGE

GT650R



TYPE
DISPLACEMENT
BORE x STROKE
COMPRESSION RATIO
MAX POWER
MAX TORQUE
FUEL SYSTEM
LUBRICATION
CLUTCH
GEAR
FINAL DRIVE
OVERALL LENGTH
OVERALL HEIGHT
OVER WIDTH
WHEEL BASE
GROUND CLEARANCE
SEAT HEIGHT
BRAKE

Liquid cooled DOHC 8-valve 90 V-twin
647cc
81,5 x 62
11,5 : 1

73,4hp (54,7kw) / @ 9,000RPM
47,6lb-ft (64,5Nm) / @ 7,500RPM

Fuel Injection
Wet Sump
Wet, Multiplate
Constant mesh 6-speed (1down 5up)
Chain

2090mm (82,28inch)

1135mm (44,68inch)

700mm (27,59inch)

1435mm (56,50inch)

165mm (6,50inch)

830mm (32,68inch)

F) 300Ø Semi floating double discs, 4 pistons calipers
R) 230Ø Single disc, 2 pistons calipers
F) 41Ø Upside down Telescopic

(Compression, Rebound damping adjustable)

R) Swing arm with Progressive Linkage Hydraulic
mono shock absorber (Preload adjustable)

F) 120/60 ZR-17 55W, R) 160/60 ZR-17 69W

17L (4,49gal)

215kg (474lbs)

TIRE
FUEL TANK CAPACITY
CURB WEIGHT

SUSPENSION



GT250R



Air/Oil cooled DOHC 8-valve 75 V-twin
249cc
57 x 48,8
10,2 : 1

27,6hp (20,60Kw) / @ 10,500RPM (Solfer muf)
15,6lb-ft (21,19Nm) / @ 7,000RPM (Solfer muf)

Fuel Injection
Wet Sump
Wet, Multiplate
Constant mesh 5-speed (1down 4up)
Chain

2090mm (82,28inch)

1130mm (44,49inch)

700mm (27,56inch)

1435mm (56,50inch)

155mm (6,10inch)

830mm (32,68inch)

F) 300Ø Semi floating double discs, 2 pistons calipers
R) 230Ø Single disc, 2 pistons calipers
F) 41Ø Upside down Telescopic

R) Swing arm with Progressive Linkage Hydraulic
mono shock absorber (Preload adjustable)

F) 110/70-17 54S, R) 150/60-17 66S (MRF)

17L (4,49gal)

188kg (414,48lbs)



MODEL

COLOR RANGE



TYPE
DISPLACEMENT
BORE x STROKE
COMPRESSION RATIO
MAX POWER
MAX TORQUE
FUEL SYSTEM
LUBRICATION
CLUTCH
GEAR
FINAL DRIVE
FRAME TYPE
OVERALL LENGTH
OVERALL HEIGHT
OVER WIDTH
WHEEL BASE
GROUND CLEARANCE
SEAT HEIGHT
CASTER
TRAIL
BRAKE

GT650P

Liquid cooled DOHC 8-valve 90 V-twin
647cc
81,5 x 62
11,5 : 1
73,4hp (54,7kw) / @ 9,000RPM
47,6lb-ft (64,6Nm) / @ 7,500RPM
Fuel Injection
Wet Sump
Wet, Multiplate
Constant mesh 6-speed (1down 5up)
Chain

2090mm (82,28inch)
1100mm (43,31inch)
785mm (30,91inch)
1435mm (56,50inch)
185mm (7,28inch)
830mm (32,68inch)

F) 300Ø Semi floating single disc, 4 pistons caliper

R) 230Ø Single disc, 2 pistons caliper

F) 41Ø Upside down Telescopic
(Compression, Rebound damping adjustable)
R) Swing arm with Progressive Linkage Hydraulic
Mono shock absorber (Preload adjustable)
F) 120/60 ZR-17 55W, R) 160/60ZR-17 69W
17L (4,49gal)
208kg (458,57lbs)

SUSPENSION

TYRE
FUEL TANK CAPACITY
CURB WEIGHT

GT250P



Air Oil cooled DOHC 8-valve 75 V-twin
249cc
57 x 48,8
10,2 : 1
27,6hp (20,60Kw) / @ 10,500RPM
15,6hp (21,19Nm) / @ 7,000RPM
Fuel Injection
Wet Sump
Wet, Multiplate
Constant mesh 5-speed (1down 4up)
Chain

2090mm (82,28inch)
1100mm (43,31inch)
785mm (30,91inch)
1435mm (56,50inch)
175mm (6,89inch)
830mm (32,68inch)

F) 300Ø Semi floating single disc, 2 pistons caliper

R) 230Ø Single disc, 2 pistons caliper

F) 41Ø Upside down Telescopic
R) Swing arm with Progressive Linkage Hydraulic
Mono shock absorber (Preload adjustable)
F) 110/70-17 54S, R) 150/60-17 66S (MRF)
17L (4,49gal)
170kg (374,79lbs)



COMING SOON !
E-SCOOTER

MODEL

ST-E3-EVA

COLOR RANGE



MOTOR TYPE
BATTERY TYPE

Brushless AC Inwheel Motor
Lithium-Ion

RATED POWER
MAX POWER

1,49Kw / @ 7000RPM
2,83Kw

CAPACITY
OPERATING VOLTAGE
TOP SPEED
RANGE
RECHARGE TIME

40Ah
48W
60km/h
90km @ 35km/h
4Hr (DOD 80%)

OVERALL LENGTH
OVERALL HEIGHT
OVERALL WIDTH
WHEEL BASE
GROUND CLEARANCE
SEAT HEIGHT

1808mm (97,24inch)
1095mm (50,79inch)
635mm (37,79inch)
1245mm (66,53inch)
115mm (6,10inch)
725mm (27,38inch)

BRAKE

F) 162Ø Single disc, 1 piston caliper
R) 171Ø Single disc, 1 piston caliper

SUSPENSION

F) Conventional Telescopic
R) Hydraulic Mono shock absorber

TIRE

F) 110/70-12 47J
R) 110/70-12 47J

CURB WEIGHT

115kg (254lbs)



COMING SOON !
STREET

MODEL

GD250N-Exiv

COLOR RANGE



TYPE
DISPLACEMENT
BORE x STROKE
COMPRESSION RATIO
MAX POWER
MAX TORQUE
FUEL SYSTEM
LUBRICATION
CLUTCH
GEAR
FINAL DRIVE
FRAME TYPE

1937mm (76,26inch)
1055mm (41,53inch)
800mm (31,50inch)
1346mm (52,99inch)
135mm (5,31inch)
790mm (31,10inch)
23,5
93,6mm (3,68inch)
F) 300Ø Petal shaped spoke mounted single disc,
2 apposed pistons caliper, Stainless mash hose
R) 230Ø Petal shaped single disc,
4 apposed pistons caliper, Stainless mash hose
F) 37Ø Upside down Telescopic
R) Dual side aluminum Swing arm with Gas
charged Hydraulic shock absorber
(Non step Preload adjustable)
F) 110/70 R17 54S, R) 150/60 R17 66S
11L (2,91gal)
150kg (330,70lbs)

SUSPENSION

TYRE
FUEL TANK CAPACITY
CURB WEIGHT

Liquid cooled DOHC 4-valve Single cylinder
249cc
73 x 59,6
12 : 1
28,4hp (21,2Kw) / @ 8,500RPM
19,25lb-ft (26,1Nm) / @ 7,000RPM
Fuel Injection
Wet Sump
Wet, Multiplate
Constant mesh, Close ratio 6-speed (1down 5up)
Chain
Steel tubular trellis perimeter main frame & Steel tubular assembly sub frame



Hyosung carries a diverse mix of motorcycle accessories to dress up your bike with some character. From custom windshields, saddlebags, floorboards, and more for your GV250, GV650 Pro, or ST7 cruiser, to slip-on exhausts from Two Brothers Racing, frame sliders, or custom levers for your GT series sportbike, Hyosung has the accessories you need. Hyosung also carries Lucas Oil products, and a variety of other accessories.



GENUINE ACCESSORIES

- **GEAR & CLOTHING**
- **SERVICE & MAINTENANCE**
- **PERFORMANCE PARTS**
- **GIFT & COLLECTION**

Our full line of accessories can be seen in our separate accessories brochure or online at www.sntmotorsusa.com.



S&T Motors America, LLC
 5815 Brook Hollow Pkwy. #C Norcross, Georgia 30071
sales@sntmotorsusa.com
 Toll Free 866. 440. 5571 | Office 770. 447. 5571 | Fax 770. 447. 55298

S&T Motors Global Distribution Network



S&T Motors America, LLC

5815 Brook Hollow Pkwy. #C Norcross, Georgia 30071



www.SNTMOTORSUSA.com



www.SNTMOTORS.ca